



image similar

描述

Datwyler offers a broad range of terminated connectors for individual customer needs.
For all patch cords figure 0 cables with 4.8x3.2 mm are used.

光学特性

| | |
|-----------------------------------|---|
| Ferrule material: | Zirconia |
| Lifetime: | 1000 connections with stable attenuation values |
| Reproducibility of the IL: | maximal +/- 0.1dB |
| Testing method IL: | IEC 61300-3-4 |
| Testing method RL: | IEC 61300-3-6 |
| 接插件型1: | LSH/APC |
| 插入损耗 (典型值) A: | 0.12 dB |
| 插入损耗 (最大值) A: | 0.25 dB |
| 回波损耗 (典型值) A: | 70 dB |
| 回波损耗 (最小值) A: | 65 dB |
| Grade, connector A (better than): | B1 |
| 接插件型2: | LSH/APC |
| 插入损耗 (典型值) B: | 0.12 dB |
| 插入损耗 (最大值) B: | 0.25 dB |
| 回波损耗 (典型值) B: | 70 dB |
| 回波损耗 (最小值) B: | 65 dB |
| Grade, connector B (better than): | B1 |

机械性能

| | |
|---|------------------------|
| Cable construction: | I-V(ZN)HH (4.8x3.2 mm) |
| Minimum bending radius: | 50 mm |
| Connector cable retention: | 100 N |
| Tensile load (IEC 60794-1-21 E1 0,33% reversible fibre elongation): | 200 N |
| Crush resistance (IEC 60794-1-21 E3, reversible fibre attenuation): | ≤ 0,2 dB |
| Impact: | IEC 60794-1-21 E4 |
| Repeated bending: | IEC 60794-1-21 E6 |
| Bending (IEC 60794-1-21 E11, reversible fibre attenuation): | ≤ 0,5 dB |
| Torsion (IEC 60794-1-21 E7, reversible fibre attenuation): | ≤ 0,1 dB |
| Operating Temperature (°C): | -10 °C - +60 °C |

订购信息

| 产品型号 | 产品 | 外护套 | 外护套颜色 | 长度 [米] |
|--------|--|------|-------|--------|
| 428811 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 1 m |
| 428812 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 2 m |
| 428813 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 3 m |
| 428814 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 4 m |
| 428815 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 5 m |
| 428816 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 6 m |

FO duplex patch cord LSH/APC - LSH/APC
E9/125 G.652.D OS2



| | | | | |
|--------|--|------|----|------|
| 428817 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 7 m |
| 428818 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 8 m |
| 428819 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 9 m |
| 428820 | FO duplex patch cord LSH/APC - LSH/APC, E9/125 G.652.D OS2 | LSZH | 黄色 | 10 m |