



image similar

产品描述

Datwyler offers a broad range of terminated connectors for individual customer needs.
For all patch cords figure "0" cables with 4.8x3.2 mm are used.

光学特性

Ferrule material:	Zirconia
Lifetime:	1000 connections with stable attenuation values
Reproducibility of the IL:	maximal +/- 0.1dB
Testing method IL:	IEC 61300-3-4
Testing method RL:	IEC 61300-3-6
接插件型1:	LCD
IL typical, connector A:	0.15 dB
IL maximal, connector A:	0.3 dB
RL typical, connector A:	35 dB
RL minimal, connector A:	30 dB
Grade, connector A (better than):	Bm2m
接插件型2:	FC-PC
IL typical, connector B:	0.15 dB
IL maximal, connector B:	0.3 dB
RL typical, connector B:	35 dB
RL minimal, connector B:	30 dB
Grade, connector B (better than):	Bm2m

物理特性

Cable construction:	I-V(ZN)HH (4.8x3.2 mm)
Minimum bending radius:	50 mm
Connector cable retention:	100 N
Tensile load (IEC 60794-1-21 E1 0,33% reversible fibre elongation):	200 N
Crush resistance (IEC 60794-1-21 E3, reversible fibre attenuation):	≤ 0,2 dB
Impact:	IEC 60794-1-21 E4
Repeated bending:	IEC 60794-1-21 E6
Bending (IEC 60794-1-21 E11, reversible fibre attenuation):	≤ 0,5 dB
Torsion (IEC 60794-1-21 E7, reversible fibre attenuation):	≤ 0,1 dB
Operating Temperature (°C):	-10 °C - +60 °C

订购信息

产品型号	产品	外护套	外护套颜色	长度 [m]
423551	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	1
423552	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	2
423553	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	3
423554	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	4
423555	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	5

FO duplex patch cord LCD - FC-PC
G50/125 OM2



423556	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	6
423557	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	7
423558	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	8
423559	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	9
423560	FO duplex patch cord LCD - FC-PC, G50/125 OM2	LSZH	orange	10