

FO patch panel OV-A / OV-T

19"/2U,不带模块

exchangeable front plate, extractable or telescopic,
depth-adjustable mounting



OV-T光纤配线架,19"/2U,不带前面板,抽屉式带伸缩滑轨,深度可调节

描述

For the termination of fibre optic cables (breakout, loose tube) - maximum of 192 fibres.
Applicable with a wide range of front plates / connector systems
(see OV-A / OV-T 2U accessories).

交付范围

Box, strain relief with M25 (2U) cable gland,
splice tray holder and adhesive fibre fixation (3 pcs.)
Please order the front plate separately.
Please order the front plate separately.

属性

外壳: 金属,抽屉式结构(OV-A)或者抽屉带伸缩式滑轨(OV-AT),锁定式结构设计
机架安装: 箱体根据19"安装机架可调节适当的安装深度(5档,最大50 mm)
安装支架颜色: 近似于RAL 7035或不锈钢
标签记号: 带编号的前面板(丝网印刷)(单独订购)
容量: 高达192芯
应力消除: 线缆扎带和螺纹线缆接头以及线缆分支器用来消除应力
线缆进线: 左后方和右后方进线(空白部分会有盲孔塞安装,一个带M20和M25槽孔的直线线缆进线面板 - 产品编号417561)
尺寸: 19"/2U, 深度254 mm
连接器系统
适配器: ST, FC, SCD, SC, LSH, LCD (取决于前面板)

订购信息

产品型号	产品	颜色	单位	Note
416960	Splice box OV-T	浅灰色		without front plate
416965	Splice box OV-T	浅灰色	1 个	without front plate
416977	Splice box OV-T	银色		without front plate
416959	Telescopic slides for upgrading OV-A to OV-T			
418098	Label for OV-A and OV-T, aluminium, length 420 mm			