

Wall-Mount Racks Premium DWMR

19"/6U, 9U, 12U, 15U and 18U
with glass front door & steel rear wall



Wall-Mount Rack Premium DWMR, 9U, 600 x 500 mm

DESCRIPTION

The Datwyler Wall-Mount Racks are designed to accept patch panels, active components and other data network equipment. They offer an extended access level from all sides thanks to removable (and lockable) side panels.

SCOPE OF DELIVERY

Fully assembled and packed, including 2 keys and drilling template

MECHANICAL PROPERTIES

Base frame:	Welded sheet steel frame (1.25 mm)
Protection class:	IP 30
Maximum Load [KG]:	40
Front door:	With tinted security glass and swivel handle lock, 1-point locking, DIN single-profile cylinder, up to 180° aperture angle, can be hinged right or left (easy to change)
Rear door:	Removable rear panel, with 150 x 56 mm knock-out panel and pre-punched holes for wall-mount installation (cabinet can also be installed without rear panel)
Side panels:	Removable, locks with universal key
Mounting profile:	1 pair of adjustable 19" vertical profiles (front), 19" rear plane (fix)
Bottom Panel:	Integrated standard steel panels with 150 x 56 mm hole, covered with sliding blind panel with butterfly nuts
Top Panel:	Integrated standard steel panels with 150 x 56 mm hole, covered with sliding blind panel with butterfly nuts
Feet:	(none)
Earthing:	pre-installed flat earthing kit
Bayable:	no

VERSIONS

Article No.	Product	Maximum load [kg]	Weight [kg]	Colour	Height	Height [mm]	Width [mm]	Depth [mm]
195033	DWMR, 9 U, 491 x 600 x 500 mm	40	23	light grey	9 U	491	600	500
195037	DWMR, 9 U, 491 x 600 x 600 mm	30	26	light grey	9 U	491	600	600
195034	DWMR, 12 U, 642 x 600 x 500 mm	40	26	light grey	12 U	642	600	500
195038	DWMR, 12 U, 642 x 600 x 600 mm	30	29	light grey	12 U	642	600	600
195035	DWMR, 15 U, 758 x 600 x 500 mm	40	30	light grey	15 U	758	600	500
195039	DWMR, 15 U, 758 x 600 x 600 mm	30	33	light grey	15 U	758	600	600
195036	DWMR, 18 U, 891 x 600 x 500 mm	40	36	light grey	18 U	891	600	500
195040	DWMR, 18 U, 891 x 600 x 600 mm	30	39	light grey	18 U	891	600	600
195099	DWMR, 9 U, 491 x 600 x 500 mm	40	23	black	9 U	491	600	500
195103	DWMR, 9 U, 491 x 600 x 600 mm	30	26	black	9 U	491	600	600
195100	DWMR, 12 U, 642 x 600 x 500 mm	40	26	black	12 U	642	600	500
195104	DWMR, 12 U, 642 x 600 x 600 mm	30	29	black	12 U	642	600	600
195101	DWMR, 15 U, 758 x 600 x 500 mm	40	30	black	15 U	758	600	500
195105	DWMR, 15 U, 758 x 600 x 600 mm	30	33	black	15 U	758	600	600
195102	DWMR, 18 U, 891 x 600 x 500 mm	40	36	black	18 U	891	600	500
195106	DWMR, 18 U, 891 x 600 x 600 mm	30	39	black	18 U	891	600	600
195411	Spare key	40 kg						