

KU-TC Plus Cat.6_A (IEC) tool-less, compact

RJ45 module, unshielded, Category 6_A (IEC)



KU-TC Plus Cat.6_A (IEC) RJ45 module, tool-less, unshielded, with dust shutter



MECHANICAL PROPERTIES

Solid copper wire:	0.42 mm (AWG 26) to 0.65 mm (AWG 22)
Re-connection:	for AWG 22, AWG 23 and AWG 24 when using the same or bigger wire diameter
Stranded copper wire:	AWG 26/7 up to AWG 23/7, re-usable once
Diameter over insulation:	0.70 mm to 1.40 mm
Temperature range	storing: -40° C to +70° C during installation: -10° C to +60° C in operation: -20° C to +60° C

GENERAL PROPERTIES

Termination: Wire guides with colour coding in accordance with T568-A and B

STANDARDS

Cat./Class	Cat.6 _A / Class E _A
Standards	IEC 60603-7-41 (Cat.6 _A unshielded, 500 MHz) IEC 60512-99-002 (4PPoE) ISO/IEC 11801:2002 / Amd.2:2010 EN 50173-1 TIA/EIA 568-B.2-10:2008

VERSIONS

Article No.	Product	Colour	PU
418074	RJ45 module KU-TC Plus Cat.6 _A (IEC) tool-less, unshielded, with dust shutter	white	12 pcs.
418075	RJ45 module KU-TC Plus Cat.6 _A (IEC) tool-less, unshielded, with dust shutter	black	12 pcs.