

Description Image Quantity DuraAir Multi 12x 5/3.5 + 1x 14/10 mm Micro-duct bundle for pole mounting with 12 micro-ducts 5/3.5 mm with 1 micro-duct 14/10 mm Weight: 520 kg/km Packaging: 1000 m on cable reel 1 = Elementary (outer) duct, 5/3.5 mm 2 = Secondary (inner) duct, 14/10 mm $3 = Outer sheath, Ø 31 mm \pm 2 mm$ 4 = Messenger, 11 mm ± 1 mm DuraAir Drop 1x 5/3.5 mm Polyester yarn Micro-duct for the connection between micro-duct bundle and building with 1 micro-duct 5/3.5 mm Weight: 60 kg/km Packaging: 500 m on cable reel 1 = Elementary duct, 5/3.5 mm 2 = Inner sheath Ø 8 \pm 0.5 mm, thickness 1.5 \pm 0.2 mm 3 = Outer sheath \emptyset 10 ± 1.5 mm, thickness 1.0 ± 0.5 mm Branch-off duct closure Protects exposed connections between DuraAir Multi and DuraAir Drop Accommodates up to 3 branch-off connections Operating temperature: -40°C to +95°C Water tight **Anchoring clamp** to fix DuraAir Multi to end or corner point poles ACFO 12 **Anchoring clamp** to fix DuraAir Drop to end or corner point poles ACFO 10



Description	Image	Quantity
Suspension clamp to fix DuraAir Multi to middle poles		
Suspension clamp to fix DuraAir Drop to middle poles		
Pole fixing bracket Fixed on pole by 2 metal strips (20 mm). Supports up to 3 anchoring clamps		
Stainless steel tape 20 x 0.4 mm SB204 Length: 50 m per roll Edges rendered blunt Comes with a plastic recyclable dispenser		
Buckle for stainless steel tape for stainless steel tape 20 x 0.4 mm		
House roof entry kit Heat shrink sealing of micro-duct or cable entering roof. Up to 6 cables/ducts of 8 to 18 mm		



Description	Image	Quantity
Jacket stripping tool for DuraAir Multi for easy, quick and safe jacket removal at the place of branch-off		
Messenger separator for easy and clean seperation of messenger from the bundle jacket		
Longitudinal cutter for DuraAir Multi to open longitudinally jacket of the bundle window at place of branch-off	And the state of t	
Micro-duct cutter for precise and sharp cut of micro-ducts. Sharp edge cut is essential for correct duct connections.		
Ratchet tensioner tool to bend, tension and fix stainless steel tape around the pole		
FO Outdoor ZT S-Micro 1x4 E9/125 G.652.D BLO for the application in micro-ducts 5/3.5 mm, metal-free, non-armoured, longitudinally watertight. Sheath colour: black Sheath Ø: 2.4 mm Maximum length: 4000 m Article No. 19343400FZ		
FO Outdoor ZT S-Micro 1x12 E9/125 G.652.D BLO for the application in micro-ducts 5/3.5 mm, metal-free, non-armoured, longitudinally watertight. Sheath colour: black Sheath Ø: 2.4 mm Maximum length: 4000 m Article No. 19346000FZ		
FO Outdoor ZT S-Micro 1x24 E9/125 G.652.D BLO for the application in micro-ducts 5/3.5 mm, metal-free, non-armoured, longitudinally watertight. Sheath colour: black Sheath Ø: 2.4 mm Maximum length: 4000 m Article No. 19343300FZ		



Description	Image	Quantity
FO Outdoor wbKT Micro 4x12 E9/125 G.652.D for the application in micro-ducts 14/10 mm, metal-free, non-armoured, longitudinally watertight. Sheath colour: black with 2 orange stripes Sheath Ø: 6.6 mm Maximum length: 4000 m Article No. 19023000FZ		
FO Outdoor wbKT S-Micro 8x12 E9/125 G.652.D for the application in micro-ducts 14/10 mm, metal-free, non-armoured, longitudinally watertight. Sheath colour: black with 2 orange stripes Sheath Ø: 6.6 mm Maximum length: 4000 m Article No. 19215900FZ		
FO Outdoor wbKT S-Micro 6x24 E9/125 G.652.D for the application in micro-ducts 14/10 mm, metal-free, non-armoured, longitudinally watertight. Sheath colour: black with 2 orange stripes Sheath Ø: 6.5 mm Maximum length: 4000 m Article No. 19450000FZ		
FO Outdoor wbKT S-Micro 9x24 E9/125 G.652.D for the application in micro-ducts 14/10 mm, metal-free, non-armoured, longitudinally watertight. Sheath colour: black with 2 orange stripes Sheath Ø: 8.4 mm Maximum length: 4000 m Article No. 19262500FZ		

DuraAir installation	
DuraAir Drop installation	
Opening of DuraAir Multi	