

ELEVATOR TRAVELLING CABLES

FL – PVC – H05V3V3H6-F

Elevator travelling cable – Low rise



PRODUCT INFORMATION

APPLICATION	Elevator travelling cable for indoor and panoramic elevators	
INSTALLATION	Follow instructions in Datwyler manual for proper handling and installation Suspension device: LZ 1009 Loop diameter: natural loop	
CONSTRUCTION	Conductors: Insulation: Support members: Outer sheath:	flexible bare Cu strands class 5 acc. to IEC/EN 60228 PVC none PVC
MECHANICAL PROPERTIES	Free suspension length: Travel speed: Operating temperature: Overall dimension (approx.): Total weight (approx.): Copper content:	max. 45 m max. 4 m/s -15 to +70 °C 57.6 x 4.4 mm 479 kg/km 192 kg/km
ELECTRICAL PROPERTIES	Rated voltage U_0/U :	300/500 V
PROPERTIES OF DATA ELEMENTS	no data elements	
FIRE PERFORMANCE	Flame propagation:	IEC/EN 60332-1-2
COLOUR CODE	Cores: Outer sheath:	black, white numbered 1-19, 1 green-yellow grey
STANDARD	EN 50214	

Article no.	Type	No./size of conductors
148786	6777-F	20 G 1.00 mm ²