


ELEVATOR TRAVELLING CABLES

FM – PVC

Elevator travelling cable – Mid rise



PRODUCT INFORMATION

APPLICATION	Elevator travelling cable for indoor and panoramic elevators	
INSTALLATION	Follow instructions in Datwyler manual for proper handling and installation Suspension device: LZ 1006 Loop diameter: natural loop	
CONSTRUCTION	Pairs 0.50 mm ² : Support members: Outer sheath:	PE, Al/PETP foil shield (FTP) high tensile fibres PVC
MECHANICAL PROPERTIES	Free suspension length: Travel speed: Operating temperature: Overall dimension (approx.): Total weight (approx.): Copper content:	max. 80 m max. 6.3 m/s -15 to +70 °C 54.1 x 5.6 mm 447 kg/km 148 kg/km
ELECTRICAL PROPERTIES	Rated voltage U_0/U : Pairs 0.50 mm ² :	300/300 V
PROPERTIES OF DATA ELEMENTS	Pairs 0.50 mm ² :	see type 6651-F
FIRE PERFORMANCE	Flame propagation:	IEC/EN 60332-1-2
COLOUR CODE	Pairs 0.50 mm ² : Outer sheath:	black, white numbered 1-24 grey
STANDARD	With reference to EN 50214	

Article no.	Type	No./size of conductors
168185	8507-F	12 x 2 x 0.50 mm ² (FTP)