


## ELEVATOR TRAVELLING CABLES

### FH – PVC

Elevator travelling cable – High rise



## PRODUCT INFORMATION

<b>APPLICATION</b>	Elevator travelling cable for indoor and panoramic elevators	
<b>INSTALLATION</b>	Follow instructions in Datwyler manual for proper handling and installation Suspension device: LZ 4001 Loop diameter: natural loop	
<b>CONSTRUCTION</b>	Conductors: Insulation: Pairs 0.75 mm <sup>2</sup> : Support members: Outer sheath:	flexible bare Cu strands class 5 acc. to IEC/EN 60228 PVC PE, Al/PETP foil shield (FTP) steel ropes, Ø 2.5 mm PVC
<b>MECHANICAL PROPERTIES</b>	Free suspension length: Travel speed: Operating temperature: Overall dimension (approx.): Total weight (approx.): Copper content:	max. 220 m max. 12 m/s -15 to +70 °C 64.3 x 9.9 mm 1037 kg/km 343 kg/km
<b>ELECTRICAL PROPERTIES</b>	Rated voltage U <sub>0</sub> /U: Cores 1.00 mm <sup>2</sup> : Pairs 0.75 mm <sup>2</sup> :	 300/500 V 300/300 V
<b>PROPERTIES OF DATA ELEMENTS</b>	Pairs 0.75 mm <sup>2</sup> :	see type 6651/3-F
<b>FIRE PERFORMANCE</b>	Flame propagation:	IEC/EN 60332-1-2
<b>COLOUR CODE</b>	Cores 1.00 mm <sup>2</sup> : Pairs 0.75 mm <sup>2</sup> : Outer sheath:	black, white numbered 1-29, 1 green-yellow black, white numbered 1-4 grey
<b>STANDARD</b>	With reference to EN 50214	

Article no.	Type	No./size of conductors
184645	8846-F	30 G 1.00 + 2 x 2 x 0.75 mm <sup>2</sup> (FTP)