


ELEVATOR TRAVELLING CABLES

FL – PVC

Elevator travelling cable – Low rise



PRODUCT INFORMATION

APPLICATION	Elevator travelling cable for indoor and panoramic elevators	
INSTALLATION	Follow instructions in Datwyler manual for proper handling and installation Suspension device: LZ 1006 Loop diameter: natural loop	
CONSTRUCTION	Conductors: Insulation: Coaxial cable: Support members: Outer sheath:	flexible bare Cu strands class 5 acc. to IEC/EN 60228 PVC 75 Ω none PVC
MECHANICAL PROPERTIES	Free suspension length: Travel speed: Operating temperature: Overall dimension (approx.): Total weight (approx.): Copper content:	max. 45 m max. 4 m/s -15 to +70 °C 42.3 x 6.5 mm 438 kg/km 111 kg/km
ELECTRICAL PROPERTIES	Rated voltage U_0/U : Cores 0.75 mm ² :	300/500 V
PROPERTIES OF DATA ELEMENTS	Coaxial cable:	see type HF-2122-F
FIRE PERFORMANCE	Flame propagation:	IEC/EN 60332-1-2
COLOUR CODE	Cores 0.75 mm ² : Coaxial cable: Outer sheath:	black, white numbered 1-11, 1 green-yellow grey grey
STANDARD	With reference to EN 50214	

Article no.	Type	No./size of conductors
185358	8798-F	12 G 0.75 mm ² + 1 CX 75 Ω